

CORROSIVE SALT REMOVER AND PROTECTANT

Description and Use

- * Removes salt deposits from trucks, metals, and sensitive surfaces.
- * Flush brine tanks and lines to prevent corrosive salt build-ups in sumps, spray bars and nozzles.

Advantages

- * Will not etch glass
- * Prevents damage to paint caused by salt
- * When used as directed, safe for painted surfaces and polished aluminum
- * Leaves coating that prevent soil redeposit
- * Biodegradable and reclaim friendly

Limitations

- * Undiluted product should not be used on chrome.

Technical Data

Appearance & Odor: Straw colored liquid, pleasant odor.
Physical State: Liquid
pH: <2.0
Boiling Point: 210° F
Freezing/Melting Point: N/A
Specific Gravity (water =1): 1.092
Evaporation Rate: As water.
Solubility in Water: Complete

Surface and Air Temperatures

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

Pre-Testing

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

Dilution

- 10:1 dilution for a difficult clean
- 10:1 - 30:1 dilution for routine maintenance
- Undiluted - 4:1 for extreme salt build-up test

Testing is recommended for the strength needed for the situation before cleaning.

Suitable Substrates

Aluminum, stainless steel (non-coated), fiberglass, rubber, painted surfaces

Application Instructions

When cleaning frames, undercarriages, aluminum, painted surfaces and wiring harness areas, the product is best applied using a pressure washer. Apply the product to the surface twice, without rinsing between applications. Leave on for at least a five minute dwell time per application. Do not exceed 120° F when applying product. It is recommended not to let product dry on the surface. Craftsmanship determines the appropriate pressures for rinsing. A thorough rinse job is always recommended, however, our chemistry never requires flooding a wall. Pressures that mark or damage the surface should be avoided. When in doubt, follow the manufacturers recommended P.S.I. for the substrate on which you are working. Two step application is an effective application method for quick release of stains, neutralizing the product and a brighter surface. Apply the ConSalt Remover let dwell for five minutes then apply Truck Wash Supreme SC. (Truck Wash Supreme SC Dilution ranges are listed in the Product Data and Specification sheet.)

Precautionary Measures

Always wear goggles and rubber gloves when handling this product. It is recommend that applicators should wear a rain suit (plastic, rubber, or PVC), boots, gloves, face shields and/or goggles to avoid splash to bare skin and eyes. The product contains Hydrochloric Acid. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. Avoid breathing fumes. Use with adequate ventilation. Keep container closed when not in use. Dispose of empty containers according to federal, state and local requirements. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.



CON SALT REMOVER

PRODUCT SPECIFICATION
CON SALT REMOVER

CORROSIVE SALT REMOVER AND PROTECTANT

Spill or Leak Procedures

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

Container Handling/Storage

Store the product in a cool dry place away from alkali / base. Do not allow this product to freeze. Vent bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue and vapors and must be handled as if full. Completely rinse drum prior to disposal.

Instructions in Case of Contact or Exposure

Eyes: Flood with water for fifteen minutes. If irritation persists, call physician.

Skin: Wash off with soap and water. If irritation persists, use a good emollient.

Inhalation: Remove to fresh air.

Ingestion: Drink copious amounts of water. Do not induce vomiting. Seek medical attention.

Notice

This product has been classified in accordance with the hazard criteria of the CFR.

Disclaimer

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

Customer Service

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

