DEALER HOT WATER PRESSURE WASHERS
Portable Electric
Direct Drive | DHS Series

This electric pressure washer is built for industrial cleaning on sites where proper ventilation may not be accessible. It features a top-fired heat exchanger that is completely accessible for troubleshooting.

DH-2003-SE0E2G

Pump
- *Direct drive triplex piston General or Mi-T-M pump with ceramic plungers*
- *Stainless-steel and brass unloader*
- *Forged brass manifold*
- *Thermal relief valve*
- *High pressure detergent injector (Available as an option on SE0E1M and SEOE2M models)*

Motor
- *Totally enclosed fan-cooled electric motor with manual thermal overload protection*
- *35-foot power cord*

Components
- *Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance*
- *No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)*

Frame
- *Reinforced powder coated steel tube frame with center balanced lifting hook*
- *13-inch flat-free tires*

Miscellaneous
- *Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F*

Unit Includes:
- *Quick connect nozzles – 0°, 15°, 25° and 40°*
- *50-foot x ⅜-inch steel wire-braided high pressure hose with quick connects, swivel and bend restrictors*
- *Adjustable pressure insulated dual lance*
- *Professional-grade insulated trigger gun with safety lock-off*

Made in USA with Globally Sourced Components

CSA CERTIFIED

DEALER HOT WATER PRESSURE WASHERS
Portable Electric
Direct Drive | DHS Series

Model Number	*PSI*	*GPM*	*Horsepower/Motor*	*Pump*	*Plug Type*	*Burner Fuel Tank Capacity*	*Burner Fuel Consumption*	*BTU per hour*	*Dimensions (LxWxH)*	*Ship Wt.*	*Net Wt.*
DH-1002-SE0E1G	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	418 lb.	295 lb.
DH-1002-SE0E1M	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	Mi-T-M	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	410 lb.	237 lb.
DH-1502-SE0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	General	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	422 lb.	299 lb.
DH-1502-SE0E1M	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	Mi-T-M	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	414 lb.	291 lb.
DH-2003-SE0E2G	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	General	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	439 lb.	316 lb.
DH-2003-SE0E2M	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	Mi-T-M	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	431 lb.	308 lb.

Options:

Part Number	*Description*	*Fits Models*
HX-0232	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1G
HX-0233	**Adjustable thermostat** - Operator is able to adjust outlet water temperature between 86°-248°F	1000 to 2000-PSI models
HX-0235	**Hour meter** - Displays number of hours unit has been in operation	1000 to 2000-PSI models
HX-0237	**Auto start/stop** - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	1000 to 1500-PSI models
HX-0238	**Time delay shutdown** - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	1000 to 1500-PSI models
HX-0239	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1M
HX-0240	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2G
HX-0241	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2M
HX-0243	**Auto start/stop** - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	2000-PSI models
HX-0244	**Time delay shutdown** - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	2000-PSI models
HX-0245	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1M
HX-0246	**300°F steam** - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1G

Accessories:

Part Number	*Description*	*Fits Models*
50-0161	**High pressure detergent injector** - High pressure water mixes with detergent to clean even the heaviest build-up	1000 to 2000-PSI models
850-0433	**50-ft. x ⅜-inch high pressure hose** - For when you need extra hose for added mobility	All models

NEMA 5-15P, 15-amp plug

NEMA 5-20P, 20-amp plug

NEMA 6-20P, 20-amp plug