

Skid Gasoline/ Diesel Dealer Hot Water Pressure Washers

<section-header>

Built with a powder coated steel frame, this series holds up on even the most demanding jobsites. It's ideal for cleaning heavy equipment and large surfaces.

PUMP

- Factory preset unloader
- Low pressure detergent injector

ENGINE

 Performance-proven gasoline engine or Kohler diesel engine with electric start – battery not included

FRAME

- Powder coated steel square tube skid frame
- Stainless-steel removable front panel
- Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

COMPONENTS

- 12V Beckett burner no need for a generator battery not included
- Stainless-steel coil wrap heat exchanger with horizontal schedule
 80 pipe coil
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Adjustable thermostat

MISCELLANEOUS

 $^{\circ}$ Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x ³/₈-inch high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

• 3 year engine

CERTIFICATION

CSA Certified – US and Canada



Skid Gasoline/Diesel

Hot Water - HDB Series - Belt Drive

GASOLINE MODEL

GASOLINE IVIC	DEL											
MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.	
HDB-3004-0H6G*	3000	3.9	389cc Honda GX390 OHV+	General	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	685 lb.	566 lb.	
+49 state engine. Not for *49 state fuel tank. All m			are required to have the HX-0287 CAI	RB compliant i	fuel tank.							
DIESEL MODE	L											
MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	PUMP	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.	
HDB-3004-0K7G	3000	3.9	9.1 HP Kohler KD440 OHV	General	1.3 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	745 lb.	626 lb.	
ACCESSORIES	:											
PART NUMBER	DESCRIPTION										FITS MODELS	
50-0170	Stack adapter – Allows 8-inch flue pipe to be installed to boiler exhaust port									All models		
850-0324	Gasket – Seals between 50-0170 stack adapter and boiler housing									All models		
AW-5740-0014	Wheel kit – 4 rubber wheels allow the unit to become portable									All models		
AW-5740-0015	Caster wheel kit - Includes 2 caster wheels and 2 rubber wheels for easier movement on flat surfaces										All models	
AW-6000-1006	Hot water equipment cover – Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover; Mi-T-M logo										All models	
AW-6000-1007	Hot water equipment cover – Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover; no logo										All models	
OPTIONS:												
PART NUMBER	DESCRIPTION									FITS MODELS		
HX-0156	Hour meter – Displays the number of hours unit has been in operation										All models	
HX-0176	Steam – Increases outlet temperature to 250°F										All models	
HX-0220	High pressure chemical, K7 – Adjustable high pressure chemical, includes float tank										All models	
HX-0221*	High pressure chemical, trapping unloader – Adjustable high pressure chemical, includes float tank										All models	

 HX-0225
 Trapping unloader – For hose runs longer than 50-foot and for cleaning elevated areas

 HX-0226
 Three-way ball valve – Allows the pressure washer to be operated from garden hose, float tank or trailer supply tank by adjusting ball lever valve

*HX-0225 trapping unloader is required when ordering the HX-0221 high pressure chemical option.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

All models

All models