

JP Series | Electric Direct Drive

The medium-duty pressure washer is the perfect selection for indoor applications and provides an exhaust-free operation.



JP-1502-3ME1

Pump

- Direct drive triplex piston AR or General pump with ceramic plungers
- Forged brass manifold
- Thermal and safety relief valves
- Low pressure detergent injector
- Stainless-steel and brass unloader with adjustable pressure

Frame

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Flat-free tires

Motor

- Totally enclosed fan-cooled electric motor
- 35-foot power cord (GFCI on 1.5 to 6.0-HP single-phase models) (10-foot power cord on 8.0-HP models)

Unit Includes:

- Variable high/low pressure nozzle (JP-1002, JP-1502 and JP-2003 models)
- Quick connect nozzles – 0°, 15° and 25° (JP-2503 and JP-3004 models)
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors (25-foot on JP-1002, JP-1502 and JP-2003 models)
- Insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip



JP-1002 and JP-1502 models



JP-2003, JP-2503 and JP-3004 models

JP Series | Electric Direct Drive



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-50P,
50-amp plug

Model Number	PSI	GPM	Horsepower/Motor	Pump	Unloader	Plug Type	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JP-1002-3ME1	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	AR	Adjustable pressure	NEMA 5-15P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1002-2ME1 *	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	Adjustable pressure	NEMA 5-15P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-3ME1	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	Adjustable pressure	NEMA 5-20P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-2ME1 *	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	Adjustable pressure	NEMA 5-20P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-2003-3ME1	2000	2.6	4.0 HP, 230V, 1Ø, 16.0A	AR	Adjustable pressure	NEMA 6-20P	36in.	37x21x24.5in.	162 lb.	112 lb.
JP-2503-1ME1	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	AR	Adjustable pressure	NEMA 6-30P	36in.	44x26x27in.	275 lb.	225 lb.
JP-2503-0ME3	2500	3.2	6.0 HP, 230V, 3Ø, 15.0A or 6.0 HP, 460V, 3Ø, 7.5A	AR	Adjustable pressure	NEMA L15-20P	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-1ME1	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	AR	Adjustable pressure	NEMA 6-50P	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-0ME3	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	AR	Adjustable pressure	NEMA L15-30P	36in.	44x26x27in.	275 lb.	225 lb.

*Pump accepts incoming water up to 175°F.

Options:		
Part Number	Description	Fits Models
CX-0005	48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0030	50-ft. x 3/8-in. non-marking hose - For when you need extra hose for added mobility	1000 to 2000-PSI models
CX-0066	460V on 6.0-HP, 3-phase model - For when you have 460V of power available	JP-2503-0ME3
CX-0067	460V on 8.0-HP, 3-phase model - For when you have 460V of power available	JP-3004-0ME3

Accessory:		
Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models